

RP-160M

Klipsch
REFERENCE
PREMIERE



90x90 HYBRID TRACTRIX HORN

Redesigned Tractrix® Horn utilizes a circular horn throat paired to a square horn mouth to further improve high-frequency response and extension, while enhancing imaging and dynamics. The compressed molded rubber construction adds high frequency damping to reduce harshness and improve detail. This creates the cleanest, most natural sound possible.

LINEAR TRAVEL SUSPENSION (LTS) TITANIUM TWEETER

A Linear Travel Suspension minimizes distortion for enhanced, detailed performance. LTS Tweeters have been a hallmark of previous Reference lines, as well as our flagship Klipsch Palladium series, making it a core component of some of the best speakers in the world.

SPUN COPPER CERAMETALLIC WOOFERS

Ceramic metallic woofers represent the pinnacle of Klipsch driver design, maintaining exceptional rigidity, and lightweight construction, for minimal cone breakup and distortion. When paired with the Tractrix Horn-loaded LTS tweeter, it provides speaker efficiency highest in its class.

ALL NEW TRACTRIX PORT

Utilizing Tractrix geometry, the all new Reference Premiere ports allows for the most efficient, fastest air transfer from the cabinet - for the cleanest, most powerful low frequency response on the market

MDF CABINET WITH BRUSHED POLYMER VENEER BAFFLE FINISH

Contemporary aesthetic with absolute durability that results in a seamless integration into any décor.

STRONG, FLEXIBLE, REMOVABLE GRILLE

Attaches magnetically for an elegant transition from powerful showstopper to discrete performance piece.

SPECIFICATIONS

| | |
|----------------------------|---|
| FREQUENCY RESPONSE | 43-24kHz +/- 3dB |
| SENSITIVITY | 95dB @ 2.83V / 1m |
| POWER HANDLING (CONT/PEAK) | 100W/400W |
| NOMINAL IMPEDANCE | 8 Ohms Compatible |
| CROSSOVER FREQUENCY | 1500Hz |
| HIGH FREQUENCY DRIVER | 1" Titanium LTS Tweeter with Hybrid Cross-Section Tractrix Horn |
| LOW FREQUENCY DRIVER | 6.5" Cerametallic Cone Woofer |
| ENCLOSURE MATERIAL | MDF |
| ENCLOSURE TYPE | Bass Reflex via rear-firing Tractrix port |
| INPUTS | Dual binding posts/bi-wire/bi-amp |
| HEIGHT | 16.67" (42.4 cm) |
| WIDTH | 8.81" (22.4 cm) |
| DEPTH | 12.86" (32.7 cm) |
| WEIGHT | 19.9 lb (9.03 kg) |
| FINISH | Ebony, Cherry |
| BUILT FROM | 2015 |

Klipsch
KEEPERS OF THE SOUND

3502 WOODVIEW TRACE INDIANAPOLIS, IN 46268 | KLIPSCH.COM

All specifications are subject to change without notice. ©2014 Klipsch Group, Inc. Klipsch, Keepers of the Sound and Tractrix are registered trademarks of Klipsch Group, Inc. registered in the US and other countries. A wholly-owned subsidiary of Vox International Corporation