

GRAVIS

Sonus faber

Class & Power



GRAVIS I

LOUDSPEAKER TYPE:

Closed box loading, down firing active subwoofer

WOOFER: 1 x 210mm (8") very long throw, treated paper cone, wide rubber surround woofer

AMPLIFIER TYPE: High linearity Class AB

POWER AMPLIFIER (MAX): 150 W rms, 250 W (peak)

FREQUENCY RESPONSE @-6DB/@-3DB (IN ROOM):
From 30/40 Hz to Fc (user adjustable)

MAINS INPUT VOLTAGE:

Factory selected, 120Vac - 60Hz or 230 Vac - 50 Hz

FUSE: T4.0A (110Vac, 60Hz); T2.0A (230V, 50Hz)

FUSE SYSTEM PROTECTION:

Output signal short circuit; Over-heating; DC fault

CONTROLS:

Independent Master and LFE volume controls; Continuously adjustable Crossover frequency (30 to 120Hz), slope 24dB/oct; Signal phase inversion switch (0/180°)

ADDITIONAL FEATURES:

Auto switch-on/off (deselectable)

AUDIO SIGNAL INPUTS:

LFE (Low Frequency Effect), single phono plug; Line level signal, single phono plug; High level signals, Neutrik 4-pole Speakon®

POWER CONSUMPTION:

0.5 W (Stand-by) 250W (Rated power)

FINISHES: Matte White, Piano Black, Wood

DIMENSIONS (HXWXD): 334x286x316mm including feet

WEIGHT (KG): 14,5

SUPPLIED ACCESSORIES:

User manual AC Power cord 10m/32.8 ft Neutrik Speakon® interconnection cable

GRAVIS II

LOUDSPEAKER TYPE:

Passive radiator bass-reflex loading active subwoofer

WOOFER: 1 x 260mm (10") very long throw, treated paper cone, wide rubber surround woofer

PASSIVE RADIATOR: 1 x 260mm (10") very long throw, treated paper cone, wide rubber surround

AMPLIFIER TYPE: High linearity Class AB

POWER AMPLIFIER (MAX): 350 W rms, 700 W (peak)

FREQUENCY RESPONSE @-6DB/@-3DB (IN ROOM):
From 25/35 Hz to Fc (user adjustable)

MAINS INPUT VOLTAGE: Factory selected, 120Vac - 60Hz or 230 Vac - 50 Hz

FUSE: T6.3A (110Vac, 60Hz); T3.15A (230V, 50Hz)

FUSE SYSTEM PROTECTION:

Output signal short circuit; Over-heating; DC fault

CONTROLS:

Independent Master and LFE volume controls; Continuously adjustable Crossover frequency (30 to 120Hz), slope 24dB/oct; Signal phase inversion switch (0/180°)

ADDITIONAL FEATURES:

Auto switch-on/off (deselectable)

AUDIO SIGNAL INPUTS: LFE (Low Frequency Effect), single phono plug; Line level signal, single phono plug; High level signals, Neutrik 4-pole Speakon®

POWER CONSUMPTION:

0.5 W (Stand-by) 450W (Rated power)

FINISHES: Matte White, Piano Black, Wood

DIMENSIONS (HXWXD): 404x356x408mm including feet

WEIGHT (KG): 21,5

SUPPLIED ACCESSORIES:

User manual AC Power cord 10m/32.8 ft Neutrik Speakon® interconnection cable

